



SUNOCO ULTRA SYNTHETIC BLEND SP/GF-6A ENGINE OILS

OVERVIEW

SUNOCO ULTRA SYNTHETIC BLEND SP/GF-6A ENGINE OILS are specially formulated using full synthetic and Group II base oils plus high-performance additive packages for superior performance benefits in gasoline fueled, flex-fueled, and GDI turbo-boosted engines. They have been engineered to meet the latest specifications of Ford Motor Company for protection from LSPI events.

APPLICATIONS

SUNOCO ULTRA SYNTHETIC BLEND SP/GF-6A ENGINE OILS protect and enhance today's modern engines utilizing GDI (gas direct injected) fuel systems and turbo chargers. These fluids meet the most demanding lubrication requirements and are recommended for most all modern passenger cars and light duty trucks. **SUNOCO ULTRA SYNTHETIC BLEND SP/GF-6A ENGINE OILS** are **ILSAC GF-6A** certified, **fully backwards compatible to GF-5** and earlier certifications, and are API "Resource Conserving" for improved fuel economy.

FEATURES & BENEFITS

SUNOCO ULTRA SYNTHETIC BLEND SP/GF-6A ENGINE OILS are uniquely designed to help extend engine life, protect against sludge and deposit formation, and protect against LSPI (low-speed pre-ignition) occurrence. These combustion events can cause premature engine wear or catastrophic failure. **SUNOCO ULTRA SYNTHETIC BLEND SP/GF-6A ENGINE OILS** also contain specialized friction-reducing additives that allow them to provide enhanced fuel economy and fuel savings.

SPECIFICATIONS

ALL VISCOSITY GRADES - API SP, SN, SN PLUS, SM, SL, SJ • ILSAC GF-6A, GF-5 • CHRYSLER MS-6395

SAE 5W-20 - FORD WSS-M2C945-B1, WSS-M2C960-A1

SAE 5W-30 - FORD WSS-M2C946-B1, WSS-M2C961-A1

TYPICAL PROPERTIES

PRODUCT CODES	7473	7483	7493
SAE Viscosity Grade	5W-20	5W-30	10W-30
Viscosity, cSt @ 100°C	8.2	9.9	10.9
Viscosity, cSt @ 40°C	48.7	59.7	67.2
Viscosity Index	142	152	154
Viscosity, CCS, cP @ °C	6,000 (-30)	5,400 (-30)	5,000 (-25)
Flash Point, COC °C, min	200	200	220
Pour Point, °C, max	-45	-45	-40